

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 7 : F16L 25/00, 47/06, 21/03, B29C 45/16</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/53965 (43) International Publication Date: 14 September 2000 (14.09.00)</p>
<p>(21) International Application Number: PCT/GB00/00836 (22) International Filing Date: 10 March 2000 (10.03.00) (30) Priority Data: 9907866.9 10 March 1999 (10.03.99) GB 99200712.0 10 March 1999 (10.03.99) EP (71) Applicant (for all designated States except US): RADIUS PLASTICS LIMITED [GB/GB]; Scarva Industrial Estate, Banbridge, County Down BT23 3QD (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): DEVINE, Gregory, Ian [GB/GB]; Radius Plastics Limited, Scarva Industrial Estate, Banbridge, County Down BT23 3QD (GB). (74) Agents: LUNT, Mark, George, Francis; Dibb Lupton Alsop, Fountain Precinct, Balm Green, Sheffield S1 1RZ_ (GB) et al.</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: CORRUGATED PIPE CONNECTOR AND METHOD OF MANUFACTURE



(57) Abstract

A connector (10') for corrugated pipe (20) comprises a sleeve, ledges (16) in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and a seal (22'/22'') moulded into said sleeve and being long enough to span at least two corrugations, whereby the seal will always contact a peak (30, 32) of said corrugations. Alternatively, at least two seals (22'') are moulded into the sleeve at spaced positions so that when the pipe is inserted into the connector one or other seal contacts a peak of said corrugations. A method of making such a seal comprises the steps of moulding said sleeve in a mould (100) comprising a sleeve core (54, 56) and an openable cavity (52), an aperture (66) being formed in the sleeve so moulded, and subsequently moulding said seal by injection of thermoplastic elastomer through said aperture into an annular space (80) defined between said sleeve and a seal core (54', 56') said space coinciding with said aperture.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

CORRUGATED PIPE CONNECTOR AND METHOD OF MANUFACTURE

The present invention relates to a connector for pipes and particularly for plastics ducting employed in the telecommunications industry, although also employed in drainage and electricity supply. Such ducting typically comprises flexible plastics tubing which is twin-walled, the outer wall being corrugated in order to facilitate flexing of the pipe or tubing during installation in the ground.

Such tubing is generally made in lengths (typically six-metre lengths) requiring that they be interconnected during installation.

Because the ducting is merely providing a housing for other cables or conduits, there is no especial requirement either for the joint to be strong or for the seal between two connected pipes to be absolute. Nevertheless, it would of course be preferable if at least the seal could be absolute but a more pressing requirement is that the ducting should be inexpensive to manufacture and install.

A joint between adjacent lengths of such ducting is presently effected by installing at each end of the length of ducting a seal element in the form of a sealing ring which is disposed in one of the corrugations of the ducting at a small distance from each end. The seal is normally an elastomeric material and has a relatively deep profile so that it can be seated securely between adjacent corrugations. A connector is provided in the form of a plastics sleeve which has internal teeth. When the sleeve is pressed over the end of the ducting, the teeth engage one or more of the corrugations, thereby providing resistance to pull out of the ducting from the sleeve. In the field, it is therefore only necessary for an installer to insert one length of ducting into the ground after the other and pressing the sleeve over the exposed end of the previously laid ducting (although this can also be done in the factory so that the ducting is supplied with one end connected to a connector). Finally the next length of ducting is inserted into the other end of the connector. The connector sleeve has a surface adapted to bear against the seal and compress it and deform it against the surfaces of the corrugations.

The sleeve is normally made of deformable plastics material such as polypropylene so that the teeth snap over the corrugations. There is normally a central ledge or rib within the sleeve so that there is a positive stop in the centre of the sleeve to allow the user to know when the pipe is pressed fully home in the sleeve. Thus the sealing ring is generally placed, not in the first or second corrugation from the end of a length of ducting, but spaced therefrom by several corrugations so that the corrugations between the end of the pipe and the sealing ring can be employed for being gripped by the teeth. This avoids the necessity of the teeth of the ducting passing over the sealing ring which might have a tendency either to damage the sealing ring or possibly to dislodge it from the corrugation in which it is placed and possibly prevent an effective seal being formed. However, by disposing the seal at a distance from the end of the pipe means that the seal is actually close to the end of the connector. This has the effect of potentially enabling the seal to be broken when a section of pipe including a connection is bent, as is frequently required when the pipe needs to go around corners, objects etc. In this event, it would be advantageous if the seal was deep within the connector so that the distorting effect of the pipe bend would be minimised.

A further disadvantage with the present method is that the forming of the joint is a two-step process. The first step is completed in the factory when a sealing ring is positioned over each end of a length of ducting and the connector is inserted at one end. The second step is effected in the field when the joint is completed by insertion of the free end into the sleeve. A further corollary problem is that, when the ducting is cut to an appropriate length, the installer must position a new sealing ring at the appropriate distance from the cut end, and this may not be completed properly and is in any event a further installation step.

A yet further disadvantage is that the seal rings are expensive components and are much larger than is absolutely necessary to effect the required seal. They are only so bulky as presently arranged so as to ensure that they remain in place in the appropriate corrugation and are not dislodged during insertion of the pipe end into the connector sleeve.

Thus, it is an object of the present invention to provide a connector sleeve and a method of making a connector sleeve so that these problems are solved or at least their effects are mitigated.

5

In accordance with the present invention, there is therefore provided, in a first aspect, a joint between a connector for corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and a seal moulded into said sleeve and
10 being long enough to span at least two corrugations, whereby the seal will always contact a peak of said corrugations.

In a second aspect, the present invention provides a joint between a connector for corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in
15 the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and a seal moulded into said sleeve at a position thereof such that when the pipe is fully inserted into the connector the seal contacts a peak of said corrugations.

In a third aspect, the present invention provides a joint between a connector for
20 corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and at least two seals moulded into said sleeve at spaced positions thereof such that when the pipe is inserted into the connector one or other seal contacts a peak of said corrugations.

25

In a fourth aspect, the present invention provides a connector for the joint as defined above.

In a fifth aspect, the present invention provides a connector for corrugated
30 pipe, the connector comprising a sleeve, ledges in the sleeve to engage with the pipe to prevent pull-out of the pipe from the sleeve, and a thermoplastic elastomeric seal moulded

into said sleeve.

In a sixth aspect, the present invention provides a method of making a connector for corrugated pipe, the connector comprising a sleeve, ledges in the sleeve to engage with the pipe to prevent pull-out of the pipe from the sleeve, and a thermoplastic elastomeric seal disposed in said sleeve, wherein said method comprises the steps of moulding said sleeve in a mould comprising a sleeve core and an openable cavity, an aperture being formed in the sleeve so moulded, and subsequently moulding said seal by injection of thermoplastic elastomer through said aperture into an annular space defined between said sleeve and a seal core, said space coinciding with said aperture.

Said sleeve core may be different from said seal core. Preferably, however, said sleeve and seal cores are the same core, wherein said core has sections collapsible from one diameter for forming said sleeve to a smaller diameter for forming said seals.

The openable cavity employed for moulding the sleeve may be different from the openable cavity for forming the seal, and in which event said aperture may be formed by a stud in said sleeve forming cavity. Preferably, however, said cavity is the same cavity in each step and said aperture is formed by a retractable pin in one or both of the cavity or sleeve core.

In this way it is feasible to mould the entire connector in a single mould in two sequential steps.

The invention is further described hereinafter, by way of example, by reference to the accompanying drawings, in which:

Figure 1 is a side view, partly in section, of a prior art joint, but embodying seal arrangements in accordance with the present invention;

Figure 2 is a perspective view, partly cut away, of a connector in accordance with the present invention; and

Figures 3a and b are sections through moulds for forming connectors in

accordance with the present invention.

With reference to the drawings, a prior art connector 10 comprises a plastics sleeve 12 having a mouth 14 and teeth 16 formed on internal surfaces of the sleeve 12. A central rib 18 divides the sleeve 12 into two ends. A corrugated pipe 20 has an elastomeric sealing ring 22 disposed in annular groove 24 between adjacent corrugations 26 of the pipe 20. The groove 24 is, in this case, the sixth groove from open end 28 of the pipe 20.

The pipe 20 is manufactured from twin-wall plastics material, such as high-density polyethylene, co-extruded with the outer wall which is substantially simultaneously corrugated (the inner wall remaining smooth. This construction of ducting provides crush strength for the ducting so that cabling carried by the ducting is physically protected, while at the same time providing great flexibility for the ducting so that it can be bent to tight radiuses. The inner layer of the ducting is smooth, however, so that insertion of cabling is facilitated.

In manufacture, the ducting is made in six-metre lengths (typically) with a sealing ring 22 being inserted at each end. Also at the manufacturing site a sleeve connector 10 is slid over one end of the pipe 20 so that each length of pipe 20 is supplied with a sealing ring 22 at each end and a connector 10 at one end. Thus assembly in the field is merely a question of pushing the "seal end" of one pipe into the "connector end" of another pipe. Teeth 16 are positioned so as to engage corrugations 30,32, the material of the sleeve 12, and of the pipe 20, being such that the teeth and/or corrugations deform when the sleeve is pushed over the corrugations of the pipe 20 and the teeth snap back behind the corrugations.

Turning to Figure 2, an embodiment of the present invention is shown, in which seal elements 22' are here moulded into connector 10' adjacent central rib 18. Indeed this is also shown at the bottom of Figure 1 where the size of the seal can be compared with the prior art seal 22. It is possible to have the seal at this depth within the sleeve because, since the seal is mounted in the connector and not on the pipe, there is no

risk of dislodging the seal or damaging it during insertion of the pipe in the sleeve.

Although shown close to the central rib 18, there is nothing to prevent the seal being positioned elsewhere, should that be desired, although the seal needs to have an axial length at least equal to the pitch of the corrugations so that the surface of the corrugations will always be in contact with the seal. Indeed the seal could be formed along most of the length of the sleeve, if desired. However, there are two exceptions to this general rule. The first is where the seal 22' is disposed at some fixed distance from the rib 18 so that, assuming the pipe is always cut in a groove 24, it can always be guaranteed that a corrugation 26 is at the same distance from the end of the pipe as the seal 22' is from the rib 28. Thus the seal could in this instance be very short. The second situation is to have at least two seal rings moulded into the sleeve 12 separated from one another by half a pitch length of the corrugations so that, whatever position the pipe is in relation to the sleeve 12, at least one of the seal rings will be in contact with a corrugation. This is shown at 22" in Figure 1.

Turning to Figures 3a and b, a mould 100 comprises an openable cavity 52 and two core parts 54,56. A port 58 in the cavity 52 gives access to an annular space 60 defined between the cores 54,56 and cavity 52 through which thermo-plastic polymer such as polypropylene can be injected to form the sleeve 12. The cavity 52 has two studs 64 which form apertures 66 in the sleeve 12.

Referring to Figure 3b, the apertures 66 are arranged to coincide with port 70 in cavity 52' whereby thermo-plastic elastomer may be injected through the apertures 66 in the sleeve 12 into annular spaces 80 so as to form seals 22'. Preferably, the seals 22' are adjacent a central rib 28, so that, assuming the core parts 54,56 split in a radial plane coincident with the rib 18, only those parts of the core which form the seals 22' are dragged over the seals 22' when the cores are separated and the cavity opened. However, this is not essential since the intruding depth of the seal 22', 22" into the internal surface of the sleeve 12 does not have to be large. Therefore, once solidified, the sleeve with the seal in place could simply be sprung over and off the cores 54,56. However, a further advantage with

disposing the seal close to the rib is that its position relative to the corrugations, assuming the pipe is always cut in a groove, is assured, and the length of the seal need not be long to ensure effective sealing against a corrugation as long as the pipe is pressed fully home against rib 18.

5

Connector 10' could be manufactured by known techniques where cavity 52 and cores 54,56 are both different from cavity 52' and cores 54',56'. However, in the case of cavity 52, this can be arranged the same as cavity 52' if studs 64 take the form of retractable pins. Such retractable pins could be in the cavity 52 or in the cores 54,56.

10 Similarly, the cores 54,56 can be the same as the cores 54',56' if the cores are provided with sections 82 having variable diameter so that, while the sleeve 12 is being moulded, the diameter of sections 82 is the same as the rest of the core 54,56 (although section 82 might even more preferably have an enlarged diameter so as to form a groove in the internal surface of the sleeve 12 to form a seal for the seal). However, when the seals 22' are being moulded, the section 82 is contracted so as to have a reduced diameter and form the spaces for the seals 22'. In this event, the retractable pins may be in the cavity 52, coinciding with injector 70 which the pins, when extended, serve to close, but open when they are retracted. However, they could be in the cores 54,56 forming part of the retractable diameter sections 82.

15
20

In this way, the entire connector 10' is formed in a single piece of apparatus in a two-stage process. Finally, although the seal 22' is shown in a simple form with a rectangular section, it might advantageously have a more sophisticated form, such as in the form of a lip seal or having a serrated section.

Claims

1. A joint between a connector for corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and a seal moulded into said sleeve and being long enough to span at least two corrugations, whereby the seal will always contact a peak of said corrugations.
2. A joint between a connector for corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and a seal moulded into said sleeve at a position thereof such that when the pipe is fully inserted into the connector the seal contacts a peak of said corrugations.
3. A joint between a connector for corrugated pipe and one end of said pipe, the connector comprising a sleeve, ledges in the sleeve to engage with corrugations on the pipe to prevent pull-out of the pipe from the sleeve, and at least two seals moulded into said sleeve at spaced positions thereof such that when the pipe is inserted into the connector one or other seal contacts a peak of said corrugations.
4. A connector for the joint as claimed in claim 1, 2 or 3.
5. A connector for corrugated pipe, the connector comprising a sleeve, ledges in the sleeve to engage with the pipe to prevent pull-out of the pipe from the sleeve, and a thermoplastic elastomeric seal moulded into said sleeve.
6. A method of making a connector for corrugated pipe, the connector comprising a sleeve, ledges in the sleeve to engage with the pipe to prevent pull-out of the pipe from the sleeve, and a thermoplastic elastomeric seal disposed in said sleeve, wherein said method comprises the steps of moulding said sleeve in a mould comprising a sleeve core and an openable cavity, an aperture being formed in the sleeve so moulded, and subsequently

moulding said seal by injection of thermoplastic elastomer through said aperture into an annular space defined between said sleeve and a seal core, said space coinciding with said aperture.

- 5 7. A method as claimed in claim 7, in which said sleeve core is different from said seal core.
8. A method as claimed in claim 7, in which said sleeve and seal cores are the same core, wherein said core has sections collapsible from one diameter for forming said sleeve
10 to a smaller diameter for forming said seals.
9. A method as claimed in claim 6, 7 or 8, in which the openable cavity employed for moulding the sleeve is different from the openable cavity for forming the seal, and said aperture is formed by a stud in said sleeve forming cavity.
- 15 10. A method as claimed in claim 6, 7 or 8, in which said cavity is the same cavity in each step and said aperture is formed by a retractable pin in one or both of the cavity or sleeve core.
- 20 11. A method as claimed in any of claims 6 to 10 to make a connector as claimed in claims 4 or 5.




Fig. 1






Fig. 2

3/3



INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/GB 00/00836

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16L25/00 F16L47/06 F16L21/03 B29C45/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16L B29C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 478 123 A (KANA O SHIRO) 26 December 1995 (1995-12-26) the whole document	1-5
Y	US 4 368 904 A (LANZ WERNER) 18 January 1983 (1983-01-18) column 2, line 23 -column 2, line 33; figures 1-4	1-11
Y	US 4 410 479 A (CYRIAX WILHELM) 18 October 1983 (1983-10-18) column 4, line 11 -column 4, line 37; figures 1-11	1-11
Y	EP 0 381 981 A (HUMMEL METALLWARENFAB A) 16 August 1990 (1990-08-16) column 15, line 9 -column 15, line 57; figures 12,14,19-24	1-5
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

7 June 2000

Date of mailing of the international search report

21/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Donnelly, C

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/GB 00/00836

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 292 615 A (REHAU AG & CO) 30 November 1988 (1988-11-30) abstract; figure 1 ----	1-5
A	GB 1 477 074 A (HEPWORTH IRON CO LTD) 22 June 1977 (1977-06-22) the whole document ----	1-11
A	US 4 747 621 A (GANS LEO ET AL) 31 May 1988 (1988-05-31) abstract; figure 6 -----	1-5

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/00836

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5478123 A	26-12-1995	JP 7127780 A	16-05-1995
US 4368904 A	18-01-1983	DE 2908337 A	04-09-1980
		CH 645448 A	28-09-1984
		FR 2451122 A	03-10-1980
		GB 2043816 A,B	08-10-1980
		IT 1209748 B	30-08-1989
		JP 1309702 C	26-03-1986
		JP 55133610 A	17-10-1980
		JP 60028215 B	03-07-1985
US 4410479 A	18-10-1983	DE 2845308 A	24-04-1980
		DE 2936016 A	12-03-1981
		AT 378498 B	12-08-1985
		AT 668079 A	15-01-1985
		AU 532018 B	15-09-1983
		AU 5188979 A	24-04-1980
		BR 7906682 A	17-06-1980
		CH 643047 A	15-05-1984
		FR 2439077 A	16-05-1980
		GB 2035192 A,B	18-06-1980
		IT 1123805 B	30-04-1986
		JP 55063232 A	13-05-1980
		NL 7907705 A	22-04-1980
		NO 793248 A	21-04-1980
		SE 7908591 A	19-04-1980
		US 4552384 A	12-11-1985
EP 0381981 A	16-08-1990	DE 3903356 A	23-08-1990
EP 0292615 A	30-11-1988	DE 3717750 A	15-12-1988
		DK 99988 A	27-11-1988
		FI 881215 A	27-11-1988
		NO 881361 A	28-11-1988
GB 1477074 A	22-06-1977	AU 500717 B	31-05-1979
		AU 1072176 A	11-08-1977
		BE 838058 A	14-05-1976
		BR 7600594 A	31-08-1976
		CA 1081419 A	15-07-1980
		CS 214730 B	28-05-1982
		DD 124239 A	09-02-1977
		DE 2603393 A	19-08-1976
		DK 30576 A,B	01-08-1976
		ES 444820 A	01-09-1977
		FI 760226 A	01-08-1976
		FR 2299143 A	27-08-1976
		IE 42251 B	02-07-1980
		IT 1057104 B	10-03-1982
		JP 1281526 C	13-09-1985
		JP 52017567 A	09-02-1977
		JP 60002168 B	19-01-1985
		NL 7600937 A	03-08-1976
		NZ 179865 A	03-04-1978
		PT 64746 A,B	01-02-1976
		SE 7600996 A	01-08-1976
		SU 673160 A	05-07-1979
		ZA 7600377 A	26-01-1977

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/00836

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4747621 A	31-05-1988	NONE	